

TE 2*, TE 6-A, TE 2-M

Chucks

Ordering designation	Item no.
TE-C WZA (SDS)	00250764
Chuck for TE-CX drill bits with SDS connection end	
TE-C chuck for TE2M (SDS connection)	00354683
TE 2* has a fixed SDS ± chuck	





TE 2-M

Quick-release chuck (Jaacob)

For twist drills with cylindrical connection ends up to 13 mm diameter, for rotary drilling only

Ordering designation	Item no.
Quick-release chuck	00070639
BF-LS interchangeable quick-release chuck TE 2-M	00338905





Key-type chuck complete (not for TE 2-M)

For twist drills with cylindrical connection ends up to 13 mm diameter, suitable for clockwise and counter-clockwise rotation and high torque

Ordering designation **Key-type chuck complete** 00070640



TE-AC angular chuck TE 6, TE 6-A (not for TE 2-M)

Technical data

Drill bit size range:	5-17 mm dia. TE-CX drill bits 18-20 mm dia. TE-C-S drill bits
Rec. drill bit size range:	5–16 mm diameter
Drilling performance:	278 mm/min or 14 cm ³ /minusing 8 mm dia. drill bit in
	medium-hard concrete: ~58% of TE 14
Weight:	1.45 kg
Ordering designation	Item no

TE-AC angular chuck

Features

00070591

- Quick and easy attachment
- For drilling with or without hammering and for screwdriving



TE 2 / TE 2-M / TE 6 / TE 16 / TE 16-C / TE 25

Quick-release chuck

For cylindrical shank twist drills up to 13 mm diameter for drilling without hammering

Ordering designation		item no.
C/F-BF quick-release chuck	1	00060208
TE-C-BFH chuck spindle	2	03401003
B/BF 1/2" 3 jaw chuck	3	00090933



Bit holder

Ordering designation Item no. S-BHU75M SDS bit holder 00306013 with TE-C connection end



Quick-release chuck TE 25

up to 13 mm dia. (without hammering action).

Special chuck for twist drills with cylindrical shank up to 13 mm dia. for drilling without hammering Ordering designation Item no.

Quick-release chuck 00030201



Chucks for the TE 6-S

Ordering designation Item no

TE-C (SDS) chuck	00343100

For TE-CX/TE-C drill bits

Ordering designation

Ordering designation Item no BF-LS interchangeable quick-release chuck 00338924

Suitable for reverse rotation. For insert tools with cylindrical shanks up to 13 mm dia. (without hammering action).







