

Hilti TE 500 breaker

High performance. Low weight.

Applications

- Moderately heavy chiseling work on concrete and masonry, mainly on walls
- Channeling on concrete and masonry
- Concrete repair work
- Removing plaster and tiles
- Chiseling breaches and penetrations for pipes in walls and floors

Advantages

- More power without extra weight
- Perfect starting characteristics and high working comfort
- Stepless hammering power regulation for best results on materials of all kinds
- Side handle with full radial and axial adjustment for a secure grip in virtually any position
- Lockable switch for easy sustained operation during long periods of use



Technical data	TE 500
Rated power (W)	1100
Impact energy (joules)	7.5
Impact frequency (strokes/min.)	0 – 3180
Vibration (m/s ²)*	12.1
Weight as per EPTA 01/2003 (kg)	5.6
Dimensions, L × W × H (mm)	471 × 108 × 243

*Triaxial vibration $a_{h,cheq}$ measured as per EN 60745-2-6 prAB: 2005 with uncertainty of $k=1,5 \text{ m/s}^2$



Hilti TE 500 breaker

Ordering designation

TE 500 breaker

Item no.

274701

Equipped with: 4-meter supply cord, durable impact-resistant plastic toolbox, Hilti grease, cleaning cloth and operating instructions.

